



Todo en maquinaria de trasformaciones plásticas

Tfno. 96 656 02 52

Fax 96 656 11 46

alimaq@alimaq.com

概述 Outline	型号 Machine Type		FT750-120
	制品类型 Product Type		单层制品 mono layer product
	每小时产量 Output per hour		20 ~ 40
	最大制品容积 Max. product volume	L	250

模头系统 Die Head System	型号 Machine Type		FT750-120
	模头类型 Die Head Type		单层 mono layer
	储料缸容积 Accumulator volume	L	20
	最大射料速度 Max. injection speed	kg/sec.	1.5
	口模直径 Die diameter	mm	200 ~ 380
	壁厚控制点数 Parison control point number		100
	模头加热段数 Head heating zone		5
模头加热功率 Head heating power	KW	52	

合模系统 Clamping System	型号 Machine Type		FT750-120
	锁模力 Clamping force	KN	750
	模板间距 Platen opening stroke	mm	650 ~ 1650
	模板尺寸(宽×高) Platen dimensions(width x high)	mm x mm	1300 x 1400
	合模速度 Closing-mold speed	mm/sec.	250
开模速度 Opening-mold speed	mm/sec.	250	

下吹装置 Bottom Blowing Device	型号 Machine Type		FT750-120
	扩张行程 stretching stroke	mm	140 ~ 440
	吹气头升降行程 stroke for blow pin up and down	mm	150
	吹气头手动升降行程 stroke for blow pin manually up and down	mm	200

气动系统 Pneumatic System	型号 Machine Type		FT750-120
	气源压力 stretching stroke	MPa	1
	工作压力 stroke for blow pin up and down	MPa	0.8
	耗气量 stroke for blow pin manually up and down	M <sup>3</sup> /min.	3

壁压厚伺液控系 For The Wall Thickness Control Hydraulic Servo System	型号 Machine Type		FT750-120
	额定压力 voltage	MPa	16
	额定流量 Rating flux	L/min.	48
	液压泵电机功率 installation power for the hydraulic motor	KW	11

电源 Electrical Power	型号 Machine Type		FT750-120
	电压 Power Voltage	V	AC380V ± 10%
	频率 Frequency	HZ	50
	线制 connecting cable		三相四线制
	总装机功率 General installation power	KW	305
平均能耗 Average energy consumption	KWh	150	

水源 Water Supply	型号 Machine Type		FT750-120
	供水压力 Water supply pressure	MPa	0.5

机架 Machine Frame	型号 Machine Type		FT750-120
	升降行程 stroke for up and down	mm	520
	升降速度 speed for lup and down	mm/min.	30

液压系统 Hydraulic System	型号 Machine Type		FT750-120
	液压泵额定压力 Hydraulic pump rating pressure	MPa	16
	大泵排量 output of large pump	ml/r.	663 × 2
	小泵排量 output of small pump	ml/r.	333 + 525
液压泵电机功率 Hydraulic motor power	KW	30 × 2	

挤出系统 Extrusion System	型号 Machine Type		FT750-120
	螺杆直径(三栏, 自上而下为外层、中层、内层) Screw dia.	mm	120
	螺杆长径比 Screw Length/Dia. Ratio		30:1
	螺杆转速 Screw rotation rate	rev./min.	5.5 ~ 55
	塑化能力 Plasticizing capacity	kg/h	400(HDPE)
	机筒加热段数 Heating zone		5
	机筒加热功率 Heating power	KW	47
挤出电机功率 Driving power	KW	132	

电源 Electrical Power	型号 Machine Type		FT750-120
	电压 Power Voltage	V	AC380V ± 10%
	频率 Frequency	HZ	50
	线制 connecting cable		三相四线制
	总装机功率 General installation power	KW	305
平均能耗 Average energy consumption	KWh	150	

水源 Water Supply	型号 Machine Type		FT750-120
	供水压力 Water supply pressure	MPa	0.5

机架 Machine Frame	型号 Machine Type		FT750-120
	升降行程 stroke for up and down	mm	520
	升降速度 speed for lup and down	mm/min.	30

描述 Description	型号 Machine Type		FT750-120
	机器重量 stroke for up and down	ton.	30
	机器外形尺寸(长×宽×高) machine dimensions(L x W x H)	m	9.4×4.6×6